

# COLEMAN EQUIPMENT, INC.

## LongRanger™



**Coleman LongRanger Articulated Jib** expands the applications a jib crane can be used for. Unlike standard straight boom jibs, LongRanger consists of two connected booms. This design allows the operator to work along walls, around columns and through doorways, thereby providing for more access to your limited floor space.

### For Performance and Quality

- Heavy Duty construction for long life
- Wide variety of standard length and capacities
- 360 degree rotation at the pivots
- End mounted plate provides connections for your lifting device
- Optional internal utilities (eliminate festooning air, vacuum, and electrical lines and wires), providing continuous rotation at the pivots
- Low friction pivot bearings (so low, we provide friction brakes to fine tune drag)
- Carbon steel construction (stainless construction available)
- Multiple mounting choices available
- Secondary boom can be mounted above primary boom for low overhead clearance applications

### Specifications for Standard Models

Reach (ft.)	4'	5'	6'	7'	8'	9'	10'
LR1 Capacity	280 lbs.	182 lbs.	124 lbs.	89 lbs.	67 lbs.	56 lbs.	38 lbs.

Reach (ft.)	8'	9'	10'	11'	12'	13'	14'	15'
LR2 Capacity	330 lbs.	286 lbs.	243 lbs.	199 lbs.	164 lbs.	139 lbs.	116 lbs.	98 lbs.
LR3 Capacity *	500 lbs.	393 lbs.	317 lbs.	259 lbs.	215 lbs.	181 lbs.	153 lbs.	131 lbs.
LR4 Capacity	628 lbs.	493 lbs.	398 lbs.	326 lbs.	271 lbs.	229 lbs.	195 lbs.	167 lbs.
LR5 Capacity	1367 lbs.	1077 lbs.	870 lbs.	717 lbs.	600 lbs.	509 lbs.	436 lbs.	377 lbs.
LR6 Capacity	2700 lbs.	2400 lbs.	2200 lbs.	1857 lbs.	1551 lbs.	1313 lbs.	1123 lbs.	969 lbs.

\* Model LR3 is designed with internal vacuum lines for use with our VacUp  
Capacities are in pounds. LongRangers with larger capacities and longer booms are provided.